



Product	AMG350-4GAT-1C-1S-P120
Description	Gigabit Ethernet PoE switch, unmanaged
Port type and amount	6 Ports in total, 4 x 10/100/1000Base-TX Ports: RJ45 with 802.3at 30 W PoE, 1 x 10/100/1000Base-TX RJ45 or 100/1000Base-FX SFP Combo Port, 1 x 100/1000Base-FX SFP Port
LEDs/interfaces	
Status LEDs	2 x Power SFP, Link/Activity, RJ45 Link/Activity, PoE, Alarm
Failure relay (load capacity)	24 V (1 A)
Connector	6 pin terminal (redundant supply/relay)
Fiber type / range / budget	
Twisted pair	0 m – 100 m (Cat 6)
Fiber optics / glass fiber	see SFPs (page 63 – 64)
Supply	
Power supply	48 – 56 VDC (redundant)
Power consumption	Max. 6 watt + PoE
Permissible ambient conditions	
Operating temperature	-40 °C – +75 °C
Constructive design	
Dimensions (W x H x D)	47 mm x 144 mm x 106 mm
Assembly	Wall mounting or DIN rail
Weight	1,000 g
IP protection class	IP 40
Housing	Anodized aluminium
Technical approvals	
Basis	CE
Shipment/accessories	
Shipment	Device, terminal block, DIN rail clip, operating instructions
Accessories (order separately)	Power supplies, patch cables, SFPs



SAP no.	
AMG350-4GAT-1C-1S-P120	10008724

Others
on request